



STACKED

Space Saving Connector Technology

DUAL PORT I/O connectors are designed for applications requiring multiple connector ports with limited PCB space. Two Right Angle D-Sub connectors are stacked one on top of another, creating a single Dual Port connector with a very condensed footprint.

FEATURES & BENEFITS

- Available in 4 Industry Standard Sizes:
(Standard Density: 9 | 15 | 25 | 37)
- Available in 3 Different Connector Spacing Options
(0.625" | 0.750" | 0.900")
- Available in 6 Different Hardware Configurations
- High Temperature UL94V-0 Thermoplastic
(260C Process Temp)
- High Performance Stamped Contacts



Follow NorComp:



NORCOMP

[http:// www.norcomp.net](http://www.norcomp.net)

STACKED

Space Saving Connector Technology

0.750" SPACING

FEMALE over MALE
MALE over FEMALE
FEMALE over FEMALE
MALE over MALE

SERIES

178-YYY-313RYY1
178-YYY-413RYY1
178-YYY-513RYY1
178-YYY-613RYY1

SIZE

9 / 15 / 25 / 37 Position
9 / 15 / 25 / 37 Position
9 / 15 / 25 / 37 Position
9 / 15 / 25 / 37 Position

0.900" SPACING

FEMALE over MALE
MALE over FEMALE
FEMALE over FEMALE
MALE over MALE

SERIES

179-YYY-313RYY1
179-YYY-413RYY1
179-YYY-513RYY1
179-YYY-613RYY1

SIZE

9 / 15 / 25 / 37 Position
9 / 15 / 25 / 37 Position
9 / 15 / 25 / 37 Position
9 / 15 / 25 / 37 Position

0.625" SPACING

FEMALE over MALE
MALE over FEMALE
FEMALE over FEMALE
MALE over MALE

SERIES

189-YYY-313RYY1
189-YYY-413RYY1
189-YYY-513RYY1
189-YYY-613RYY1

SIZE

9 / 15 / 25 / 37 Position
9 / 15 / 25 / 37 Position
9 / 15 / 25 / 37 Position
9 / 15 / 25 / 37 Position



DUAL-PORT

*Ruggedized
Solutions for
Harsh Environments*

Contact us for any custom or semi-custom dual-port project.

NORCOMP

For More Information

www.norcomp.net
800-849-4450

